

Dimensions and specifications

Unit: mm

Nominal size	Expanded ID (min)	Recovered ID (max)	Recovered wall thickness (ave)	Unit of packing
AWG-24	0.81	0.68	0.20	30m
AWG-22	1.10	0.83	0.20	30m
AWG-20	1.27	1.00	0.20	30m
AWG-18	1.60	1.25	0.20	30m
AWG-16	2.10	1.55	0.23	30m
AWG-14	2.40	1.80	0.23	30m
AWG-12	2.90	2.30	0.23	30m
AWG-10	3.50	2.90	0.25	25pcs.
AWG-9	4.00	3.20	0.25	25pcs.
AWG-8	4.60	3.60	0.25	25pcs.
AWG-7	5.00	4.00	0.28	25pcs.
AWG-6	5.70	4.60	0.28	25pcs.
AWG-5	6.40	5.00	0.28	25pcs.
AWG-4	7.40	5.80	0.28	25pcs.
AWG-3	7.90	6.40	0.28	25pcs.
AWG-2	9.20	7.20	0.30	25pcs.
AWG-1	10.20	7.90	0.30	25pcs.
AWG-0	11.20	8.90	0.30	25pcs.
#10	12.70	9.70	0.38	10pcs.
#12	14.70	11.40	0.50	10pcs.
#14	16.90	13.00	0.50	10pcs.
#16	17.70	13.70	0.50	10pcs.
#20	22.00	18.00	0.50	10pcs.
#25	27.90	22.30	0.50	5pcs.
#30	33.00	25.40	0.50	1pcs.
#38	43.20	33.00	0.50	1pcs.
#48	53.30	43.20	0.50	1pcs.
5/8	21.08	16.20	0.64	5pcs.
3/4	25.40	19.40	0.76	5pcs.
7/8	29.70	22.70	0.89	1pcs.
1	33.78	25.90	0.89	*
1-1/8	38.10	29.10	0.89	*
1-1/4	42.30	32.30	0.89	*
1-3/8	46.55	35.30	0.89	*
1-1/2	50.80	38.60	0.89	*

* There is no stock of 1 to 1-1/2 sizes. Please contact us for the minimum order quantity, price, and lead time.

● Standard length is 1.2m. ● Standard color is natural. ● Please contact us for inquiry regarding compliance with AMS, UL and other standards.